

AUTO CITY SPEEDWAY
“CITY CYLINDER- V-6 SERIES”
6 (SIX)-CYLINDER CLASS
AGES-12 YRS OLD -17 YRS OLD

One-way Radios are mandatory – RACECEIVER’s

-

Parents Rule:

Attention parents! This racing class is a learning - mentoring class (Trophy Only) for young men & young women between the age of 12 & 17 years. You must be 12 years old, minimum, prior to July 4 of your race season and no older than 17 years of age. You are encouraged to join the Auto City Speedway in mentoring sportsmanship, driving skills, school academics and life experiences tied to competitive auto racing while supporting the future of Automotive Racing. Remember you are setting an example for your children, please act responsible and set a good example for them to learn from!

PLEASE NOTE. It is the young driver and parents responsibility to check and/or upgrade all personal safety equipment: a full containment seat, a head and neck restraint, a fuel cell, if used, with all of the proper check valves in place, a new fire suit including proper undergarments, gloves, socks and shoes that all meet the highest of safety ratings. It is highly recommended that all safety equipment meets the Snell rating and be SFI/1 approved. Put Safety First. The highest standard of the ACS General Rules is applicable to this class. All cars must be registered. Cars registered in this class will not be able to race in the Enduro. There will be a designated night for all new drivers to practice and get familiar with the track and rules early in the season. TBD

MAKE & BODY:

Any General Motors, Ford or Chrysler (American Brand Name) front wheel drive 6-cylinder car. No Mini Vans, Full size Vans or SUV’s allowed.

1. Six-cylinder, front wheel drive, factory fuel injection only, complete stock body and complete stock frame from front to rear. All exterior body panels will remain stock front to rear.
2. No alterations will be made unless the rules expressly state alterations are permissible.
3. No convertibles, 2 seat coupes, trucks (SUV’s) or super or turbo charged cars are allowed.
4. May secure bumpers to frame mounts with a maximum of 1/8” thick angle iron or flat stock. No heavy tubing or channel. Nothing over 1/8” thick and 4” tall. This is permissible to save teams time and the cost of purchasing OEM bumpers. Adding too much bumper support will result in the team cutting them off. Allowable is adding one piece of 1.75” x .090” (maximum size) tubing between frame horns (both front and rear) to provide a solid place to attach the chain/cable hook-up. Standard hardware cloth may be attached in front of the radiator, but no expanded steel or equivalent is allowed.

5. Both front and rear bumpers must be strapped or chained to the frame to prevent dragging. When removing the vinyl covering on the dashboard, the “ugly stuff” may be covered up with a piece of aluminum or sheet metal. Rub rails are allowable when securely mounted with carriage bolts and smooth ends.
6. Any patch work on the exterior of the car will have steel or aluminum patches. All sheet metal will be riveted or welded; no sheet metal or self-tapping screws.
7. Body must be presentable at all times. Lettering must be in good taste and neat. We encourage theme cars – ie – Cartoon Characters etc. A Best Appearing Car Award at the current year Awards Banquet.

All cars will be equipped with front and rear tow hooks, straps or chains where a wrecker can quickly and safely hoist the car so it can be towed.

ENGINES AND EXHAUST:

1. Unaltered stock ECM computers. No aftermarket computer chips or programs. Teck must be able to read ECM.
2. Cars will use OEM transmissions & engines that match the make of the car (i.e., Chevy to Chevy; Ford to Ford, etc.) No dual overhead cams allowed.
3. All cars must start with the stock ignition key or a simple push button/toggle switch. All the stock wiring to the car will remain intact. Engines and transmissions are to remain stock.
4. A stock style exhaust system complete with a muffler that exits behind the driver’s seat is mandatory. 2” maximum exhaust tubing; catalytic converter not needed.

GAS TANKS AND BATTERIES:

1. A racing fuel cell or a stock gas tank in good condition and in its stock, location is required.
2. Double check the gas lines and the tank straps, replace them if they are worn. All cars must have a shut off switch next to driver window which can easily be reached from the outside of the car.
3. Batteries must not be located in driver compartment.

COCKPIT:

1. There will be no gutting or stripping of any metal inner body panels unless the roll cage bars go all the way out to the door skin. Minor gutting of the non-cockpit body parts is allowable. For four-door cars, the driver’s side window/door post between the front and back door may be removed for roll bar clearance and added room to exit and enter the car.
A Lexan windshield is highly recommended. No rear windows.

2. A 2.5# pound fire extinguisher in working order must be securely mounted and within drivers reach **mandatory!** And must know how to work it!!

WHEELS/TIRES:

1. 7" wide wheels maximum. Safety wheels are allowed. No aluminum or offset wheels allowed.
2. All wheels and tires must be the same size. 1" lug nut required. Wheel studs must extend at least one thread beyond lug nut. All wheel weights must be removed from both the inside and outside of all wheels. No wheel spacers of any kind. Stock DOT tires only. Z rated, bias ply, trailer and recap tires are prohibited. Single ply sidewall DOT radial tires only. No Goodyear Triple Tread tires or high dollar equivalent tires will be allowed. Any 55, 60, 65, 70, 75 or 80 series radial tire 165-215. All 4 wheels must have the same size tire; no mixing of sizes. The track has the right to reject any tire.

STEERING AND SUSPENSION:

1. All steering and suspension will remain stock with no modifications, front to rear and side-to-side.
2. The wheelbase will remain within 1/4" side to side (rear steer).
3. Drivers may have a quick release steering wheel for safety. The complete stock steering assembly must remain.
4. Brake and gas pedals will remain stock. A toe clip on the gas pedal is highly recommended.
5. Struts may be taken off for inspection at any time during the event. No cutting, shortening, heating or stretching of the springs. Springs and struts must be stock for the car's make, model and year. All cars must bounce freely up and down.

SAFETY:

1. Although drivers are strongly encouraged to build and work on their own cars, if the team has little or no experience putting in a safe roll cage, contact a good welder to assist with installing a quality roll cage, racing seat, 5-point safety belts and window net mounts.
2. All cars will have a minimum of a 4-post roll cage. The minimum round or square tubing size is 1.5" x .095" thick; no exhaust tubing or old rusty well pipe allowed.
3. The rollover bar will be behind the driver's head, with the upper halo section constructed to give the driver plenty of head clearance and protection to provide safety in the event of a rollover.
4. All cars will have a minimum of 3 driver's side door bars, as well as a single or an X door bar on the passenger side.
5. A minimum 30" wide by 12" tall by 1/8" thick driver's side doorplate is required on all cars. No removal of any interior door panels except for door bar clearance.
6. All doors must be bolted, welded or chained shut.

7. The back of the seat must be secured to the horizontal back bar of the roll cage. An aluminum racing seat is mandatory.
8. Rear bars will be a maximum of 1.75" round or square tubing. The rear support bars may extend rearward from the top of the cage behind the driver, angling down to the rear of the trunk area.
9. Two bars may extend back from the middle section of the back-hoop rearward. No bars may extend through the rear of the trunk area. Drivers may have an X between the two rear diagonal bars. The rear strut towers may be supported with the back bars to help keep strut towers in place. Bars are allowed to extend through the front firewall for added leg protection for the driver. These bars may attach to the strut towers, but may not go any further forward. Front hoops are allowed for safety. 1.5" round tubing maximum. No heavy square tubing or channel.
10. Stock bumpers and all front OEM sheet metal are required.
11. All mirrors, upholstery, insulation inside and under the hood, carpet, tail lights and headlights, all loose trim on the exterior of the body, trailer hitches, and aftermarket additions must be removed from the car. Any combustible material in the driver's cockpit area must be removed.
12. The original hood and trunk latches must be removed and replaced with a quick release hood pin system. Any hatchback may be removed entirely or must be solidly welded or bolted shut.
13. All holes in the floorboard and front firewall must be covered securely with sheet metal. All sheet metal will be riveted or welded; no sheet metal or self-tapping screws.
14. Carefully vacuum all loose glass or material from the interior of the body panels. All loose rust flakes or trim must be removed from cars. Use a sledgehammer on bumpers to knock off the loose material from the undercarriage.
15. The cockpit and trunk areas must be clean and vacuumed before a car is allowed on the track.

This is a beginning class, have fun!!!